



# FIRECHIEF® ALARMS

UNOBTRUSIVE BY DESIGN



## Firechief Cavius Travel Alarm

FCTA - Part of the Firechief Alarm Home and Leisure Range

Approved to EN14604



100% TESTED



5 YEAR LITHIUM



POWERED BY  
**CAVIUS**  
TECHNOLOGY

**DANISH  
DESIGN**



reddot design award  
winner



ENGINEERED IN BRITAIN

**FIRECHIEF®**  
making the world a safer place

[firechiefglobal.com](http://firechiefglobal.com)



## PRODUCT DATA

### DEVICE TYPE:

Optical smoke alarm and motion detector device.

### USAGE:

Designed for added safety when travelling. Smoke detector to be activated when staying at hostels and hotels with low safety level. Motion sensor to be activated and device to be placed in front of door or hooked onto the backpack etc. Attack alarm to be activated in unsafe situations. Carabina clip included for easy attachment to bags, belts etc.

### FUNCTION:

Travel alarm with 3 functions:

1. Attack alarm
2. Smoke alarm
3. Motion alarm

Both smoke alarm and motion alarm mode can be activated at the same time.

### PRODUCT DIMENSIONS:

D: 35 mm. x H: 90 mm.

### PRODUCT WEIGHT:

60 gr: (including 1 x AA battery)

### OPERATION AC/DC:

DC

### BATTERY LIFE:

Minimum 5 year life in normal operating condition.

### SOUND:

Audible indicator min. 90 dB @ 1 meter in anechoic chamber.

### SOUND PATTERN:

Alarm sound is a continuous sound, sweeping from high to low tone for maximum alertness.

### VISIBLE INDICATOR:

Smoke function mode: Yellow LED Motion function mode: Green LED Alarm mode: Red LED

### PUSH BUTTON:

Push button to switch between the 3 functions:

- Smoke
- Motion
- Attack alarm by continuous press

### ISOTOPE ACTIVITY:

Absence of radioactive substances.

### WARRANTY:

10 year

### APPROVALS:

CE / EMC  
RoHS  
REACH

### BATTERY TYPE:

1 x 1,5v AA battery

### CE TESTING INSTITUTE:

ITS

### AWARDS:



reddot design award  
winner

### ASSOCIATIONS:

CAVIUS is member of the NF292 committee. CAVIUS is member of GIFSID, manufacturers' association of domestic fire safety equipment.

### OPERATING TEMPERATURE:

+4°C to +38°C (tested from 0 degrees to 55 degrees)

### OPERATING HUMIDITY:

Up to 90% RH non-condensing

### STORAGE TEMPERATURE:

-20°C to +60°C

### STORAGE HUMIDITY:

Up to 93% RH non-condensing

## MANUFACTURER

Manufacturer: Cavius Aps, DK8600



100% scale - Height 90mm

**CONTACT US ON**

**T** 0330 999 0019  
**F** 01572 770133  
**E** [sales@firechiefglobal.com](mailto:sales@firechiefglobal.com)  
Monday to Friday 8am – 5pm