

# WHEELED CARBON DIOXIDE FIRE EXTINGUISHERS

**FIRECHIEF®**  
making the world a safer place

**MODEL:  
CD30**



- Clean and highly effective
- Safe on electrical equipment
- One person operation
- One person movement
- Conforms to EN1866-1
- Certified to the Pressure Equipment Directive PED 2014/68/EU, and to the Marine Equipment Directive 2014/90/EU.



 +44 (0) 330 999 0019

 [sales@firechiefglobal.com](mailto:sales@firechiefglobal.com)

 [firechiefglobal.com](http://firechiefglobal.com)

# WHEELED CARBON DIOXIDE FIRE EXTINGUISHERS

**FIRECHIEF®**  
making the world a safer place

This fire extinguisher has been designed to be used in the industrial sector and is also suitable for use in marine and maritime field. It can be used on live electrical equipment. The wheeled fire extinguisher is intended for use in high fire risk areas, which requires high extinguisher performance levels. The unit has a strong 233B fire rating.

**MODEL:  
CD30**

All extinguishers are made from raw materials from approved suppliers. All products undergo strict quality tests to ensure high performance and excellent quality standards. All units conform to EN1866-1, and are certified to the Pressure Equipment Directive PED 2014/68/EU, and the Marine Equipment Directive 2014/90/EU.

## CO2 CARBON DIOXIDE

Carbon Dioxide is an inert gas which is charged in a cylinder in liquid form at 55 bars of pressure and at a temperature of -78°C. It is an extinguishing agent and it does not require additives or other substances to perform its function. The extinguishing action takes place from the replacement of the Oxygen necessary for combustion with inert gas. The power of the jet both removes the fuel (Oxygen) and lowers the flames; during the dispensing. The temperature difference between the dispensed liquid (-78 °C) and the surrounding environment allows the creation of condensation (CO2 snow) quickly reducing the temperature of the fire. The delivery is through a cone with diffuser. Carbon Dioxide can be used on B class fires (flammable liquids, oils and paints, etc ...) and is suitable for use on live equipment.



## Specifications

Model	CD30
Product Code	100-1021
Capacity (kg)	30
Height (mm)	1230
Cylinder diameter (mm)	230
Discharge time (secs)	28
Filled Weight (kg)	82
Working Pressure (bar)	50
Test Pressure (bar)	250
Temperature Range (°C)	-30/+60
Fire Rating	233B

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland

+44 (0) 330 999 0019

sales@firechiefglobal.com

firechiefglobal.com