

FIRECHIEF AUTOMATIC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place



APS1/S

APS2/S



APS12



APS10



APS6



APS2



APS1

MODEL:

APS1
APS2
APS6
APS10
APS12
APS1/S
APS2/S

- Designed for use in enclosed areas i.e. engine/plant rooms, switch rooms etc
- Fitted with pressure gauge for easy routine checking
- Stored pressure
- Fixing brackets included with extinguishers
- Supplied with 68°C red bulb
- 2 year guarantee



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

FIRECHIEF AUTOMATIC POWDER EXTINGUISHERS



The Firechief Automatic Powder Fire Extinguishers are designed for enclosed areas such as engine/plant rooms etc.

Containing ABC dry powder extinguishant which covers most fires involving wood/paper, flammable liquids and electrical fires. The heat-sensitive glass bulb bursts when the temperature rises to 68°C.

MODEL:

**APS1
APS2
APS6
APS10**

**APS12
APS1/S
APS2/S**



Specifications

| Model | APS1 | APS2 | APS6 | APS10 | APS12 | APS1/S | APS2/S |
|--|---|---|---|--|--|--|--|
| Product Code | 100-1004 | 100-1008 | 100-1010 | 100-1006 | 100-1007 | 100-1588 | 100-1589 |
| Description | Firechief 1kg ABC Dry Powder Automatic Extinguisher | Firechief 2kg ABC Dry Powder Automatic Extinguisher | Firechief 6kg ABC Dry Powder Automatic Extinguisher | Firechief 10kg ABC Dry Powder Automatic Extinguisher | Firechief 12kg ABC Dry Powder Automatic Extinguisher | Firechief 1kg ABC Dry Powder Automatic Extinguisher - Slimline | Firechief 2kg ABC Dry Powder Automatic Extinguisher - Slimline |
| Capacity (kg) | 1 | 2 | 6 | 10 | 12 | 1 | 2 |
| Fire Rating | n/a | n/a | n/a | n/a | n/a | n/a | n/a |
| MED Approval | NO | NO | NO | NO | NO | NO | NO |
| Coverage (m ²) | 1 | 2 | 6 | 10 | 12 | 1 | 2 |
| Recommended mounting height above risk (m) | 1.5 | 1.5 | 2 | 2 | 2 | 1.5 | 1.5 |
| Working Pressure (bar) | 15 | 15 | 15 | 15 | 15 | 15 | 15 |
| Temperature Range (°C) | (-30°C-+60°C) | (-30°C-+60°C) | (-30°C-+60°C) | (-30°C-+60°C) | (-30°C-+60°C) | (-30°C-+60°C) | (-30°C-+60°C) |
| Bulb release temp (°C) | 68 | 68 | 68 | 68 | 68 | 68 | 68 |
| Product Height (mm) | 90 | 123 | 180 | 215 | 275 | 327 | 383 |
| Product Diameter (mm) | 160 | 190 | 250 | 270 | 270 | 85 | 110 |
| Filled Weight (kg) | 2.2 | 5.5 | 8.2 | 14 | 16.1 | 2.2 | 5.5 |
| Carton Height (mm) | 270 | 270 | 360 | 425 | 465 | 350 | 425 |
| Carton Length (mm) | 170 | 190 | 260 | 275 | 275 | 100 | 390 |
| Carton Width (mm) | 170 | 190 | 260 | 275 | 275 | 100 | 260 |
| Packaged Weight (kg) | 2.5 | 5.8 | 8.5 | 14.4 | 16.4 | 2.4 | 5.8 |
| Product EAN | 5055377901561 | 5055377901578 | 5055377901585 | 5055377901592 | 5055377901608 | 5055377961022 | 5055377961039 |

*Guidance coverage likely achieved using recommended mounting height.

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland

+44 (0) 330 999 0019

sales@firechiefglobal.com

firechiefglobal.com