FIRECHIEF FIRE HOSE



MODEL:

FH19/30-B FH19/45 FH25/30

- LPCB approved to EN694
- Suitable for use in public buildings and offices
- Excellent abrasion resistance
- Made from cadmium free materials
- Resistant to a wide range of chemicals
- Outstanding UV/Ozone resistance
- Silicone free
- Good resistance to ageing
- Flexible
- 2 year guarantee
- Designed for emergency use













FIRECHIEF FIRE HOSE



Manufactured from highly modified PVC Nitrile with encapsulated high tensile polyester fibres that looks and feels like rubber but is outstandingly flexible and kink resistant.

making the world a safer place

MODEL: FH19/30-B FH19/45

FH25/30



Model	FH19/30-B	FH19/45	FH25/30
Product Code	102-1086	102-1004	102-1007
Internal Diameter (mm)	19	19	25
External Diameter (mm)	26	26	34
Length (m)	30	45	30
Weight (kg)	14.1	21.3	20
Max Working Pressure at 20°C (bar)	15	15	15
Temperature Range	-20 to +60°C	-20 to +60°C	-20 to +60°C

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland







Issued: v1March22